

## NOTES:

INTERFACE CONFORMS TO IEC 60169-36 AND CECC 22220 MCX SERIES

## ELECTRICAL:

NOMINAL IMPEDANCE: 50Ω FREQUENCY RANGE: DC TO 6 GHz

## MATERIALS:

INSULATOR: TEFLON PER ASTM-D-1710


OUTER CONTACT: BERYLLIUM COPPER PER ASTM-B-196


BODY & CONTACT: 360 ALLOY BRASS 1/2 HARD PER ASTM-B-16

## FINISHES:

CONTACT: GOLD PLATE PER MIL-DTL-45204

BODY & CRIMP SLEEVE: GOLD PLATE PER MIL-DTL-45204





**RECOMMENDED STRIPPING DIMENSIONS** 

	APPD.	T.D.	
AS EMBEDD AD THE HALL NOT B ANYONE IN A	DATE	03/17/17	
	BY	J.N.	
	DATE	03/17/17	
PROPRIETARY NOTICE THIS DRAWING AND DESIGNES AND IDEAS EMBEDDED IN THE BEDICKE TO WHICH IT RELATES AND THE METHOD FOF PRODICING THE DEVICE SHALL NOT BE EMPLOSED COMED ON PISCLOSED TO ANYONE IN ANY MANNER WITHOUT THE WRITTEN CONSENT OF AN EZ FORM COMPANY OFFICIAL	DESCRIPTION	Initial release	
THIS IN TH EMPL	REV.	_	

UNLESS OTHERWISE SPECIFIED:									
DIMENSIONS ARE IN INCHES: TOLERANCES: NONE						CALE 1:1			
					0		8		
MATERIAL: SEE NOTES									
FINISH: SE	E NOTES								
DRAWN	DATE	CHECKED	)			DATE			
J.N.	4/6/17	T.D.			4/6/	/17			
APPROVED A.T.	DATE 4/6/17	SHEET	1	OF	1		/		



EZ Form Cable Corporation 285 Welton Street

285 Welton Street Hamden, CT 06517 WWW.ezform.com

MCX STRAIGHT PLUG FOR RD316 CABLE

**A** 9W826

701958-316 DSMCX